

**Stainless steel dutch weave mesh STS304/STS316L-ASTM E2814**  
**The materials of the wires for mesh are conforming to the requirements ASTM A580.**

Mesh No.	Wire Diameter		Absolute Filtration	Nominal Filtration	Roll Width Max	Weave type
	inch	mm	µm	µm	mm	
12×64	0.0240×0.0165	0.60×0.42	260-280	250	1600	plain
12×90	0.0178×0.0120	0.45×0.30	270-300	211	1600	plain
14×88	0.0200×0.0130	0.51×0.33	255-275	250	1600	plain
14×100	0.0160×0.0110	0.40×0.28	235-260	182	1600	plain
16×120	0.0140×0.0094	0.36×0.24	180-198	150	1600	plain
24×110	0.0150×0.0100	0.36×0.25	115-128	110	1600	plain
30×150	0.0090×0.0070	0.23×0.18	90-105	90	1600	plain
40×200	0.0070×0.0055	0.18×0.14	70-80	70	1600	plain
40×340	0.0098×0.0030	0.25×0.08	78-84	75	1600	plain
50×250	0.0055×0.0045	0.14×0.11	52-57	55	1600	plain
50×280	0.0055×0.0040	0.14×0.10	50-55	50	1600	plain
80×400	0.0050×0.0028	0.13×0.07	40-45	40	1300	plain
20×250	0.0100×0.0080	0.254×0.200	100-118	100	1600	twill
30×360	0.0100×0.0060	0.254×0.152	95-105	90	1600	twill
40×560	0.0070×0.0040	0.178×0.102	75-83	65	1600	twill
50×250	0.0100×0.0080	0.254×0.200	55-60	50	1600	twill
80×700	0.0040×0.0030	0.102×0.076	35-38	35	1600	twill
200×600	0.0024×0.0018	0.061×0.046	28-32	30	1600	twill
165×800	0.0028×0.0020	0.071×0.051	25-39	25	1300	twill
165×1400	0.0028×0.0016	0.071×0.041	16-18	15	1300	twill
200×1400	0.0028×0.0016	0.071×0.041	12-14	10	1300	twill
250×1400	0.0022×0.0016	0.056×0.041	11-13	9	1300	twill
325×2300	0.0015×0.0010	0.038×0.025	8-9	5	1300	twill
400×2800	0.0011×0.0008	0.028×0.020	4-5	2	1300	twill
130×30	0.0079×0.0177	0.200×0.450	100-110	100	1300	Reverse Plain
128×36	0.0079×0.0157	0.200×0.400	80-90	80	1300	Reverse Plain
175×50	0.0059×0.0118	0.150×0.300	60-70	60	1300	Reverse Plain
290×60	0.0035×0.0090	0.090×0.230	43-51	51	1300	Reverse Plain
290×74	0.0035×0.0079	0.090×0.200	38-45	40	1300	Reverse Plain
625×105	0.0016×0.0055	0.042×0.140	23-28	25	1300	Reverse Plain
630×134	0.0015×0.0051	0.040×0.130	18-23	17	1300	Reverse Plain
720×150	0.0013×0.0043	0.035×0.110	16-20	14	1300	Reverse Plain
48×10	0.0200×0.0200	0.500×0.500	350-450	400	1300	Reverse Twill
72×15	0.0200×0.0200	0.500×0.500	250-350	300	1300	Reverse Twill
132×16	0.0140×0.0180	0.352×0.457	210-260	250	1300	Reverse Twill
132×18	0.0140×0.0179	0.355×0.455	180-220	200	1300	Reverse Twill
152×24	0.0120×0.0140	0.315×0.350	115-130	165	1300	Reverse Twill
260×40	0.0059×0.0086	0.150×0.220	80-95	125	1300	Reverse Twill
325×39	0.0059×0.0120	0.150×0.300	45-75	55	1300	Reverse Twill
345×45	0.0055×0.0090	0.140×0.230	40-65	50	1300	Reverse Twill
400×120	0.0026×0.0040	0.065×0.100	60-70	60	1300	Reverse Twill

Any interest, please feel free to contact us!

Dashang Wire Mesh

Email: sales@dashangmesh.com

Tel/Fax: 0086 318 7563319/7521333

Pho: 0086 18632807688

Industrial Woven Wire Mesh Solution!

