

*Stainless Steel Bolting Cloth is also a square mesh that uses smaller wire diameters to provide a high percentage of open area. Since the cloth generally belongs to the fine wire cloth, it is widely used in screen printing and fine particle screening, used in printing, plate making in electronics, textile, ceramics, glass and other industries, and filtration in high-tech fields such as aviation, aerospace, petrochemical, etc.*

*Stainless Steel Bolting Cloth Specifications in Stock*

Mesh No.	Wire Diameter		Opening Size		Open Area	Roll Width Max
	inch	mm	inch	mm	%	mm
16×16	0.009	0.229	0.0535	1.36	73.3	1600
18×18	0.009	0.229	0.0466	1.18	70.1	1600
24×24	0.0075	0.191	0.0342	0.869	67.2	1600
28×28	0.0075	0.191	0.0282	0.716	62.3	1600
30×30	0.0065	0.165	0.0268	0.681	64.8	1600
36×36	0.0065	0.165	0.0213	0.541	58.7	1600
40×40	0.0065	0.165	0.0185	0.47	54.8	1600
50×50	0.0055	0.127	0.0145	0.368	55.3	1600
60×60	0.0045	0.114	0.0122	0.31	53.5	1600
70×70	0.0037	0.094	0.0106	0.269	54.9	1600
76×76	0.0037	0.094	0.0095	0.241	51.8	1600
80×80	0.0037	0.094	0.0088	0.224	49.6	1600
90×90	0.0035	0.089	0.0076	0.193	46.8	1600
94×94	0.0035	0.089	0.0071	0.18	44.8	1600
105×105	0.003	0.076	0.0065	0.165	46.9	1600
120×120	0.0025	0.064	0.0058	0.147	48.5	1600
130×130	0.0017	0.043	0.0059	0.152	60.8	1600
160×160	0.0014	0.036	0.0048	0.123	59.8	1600
180×180	0.0012	0.03	0.0028	0.205	76.1	1600
200×200	0.0016	0.04	0.0034	0.0864	46.7	1600
230×230	0.0014	0.0356	0.0029	0.0737	45.5	1600
250×250	0.0012	0.03	0.0028	0.0716	49.7	1600
325×325	0.0012	0.03	0.0028	0.048	37.9	1600
400×400	0.0009	0.022	0.0016	0.0415	42.7	1600