

**Non ferrous metal (Brass/Bronze/Copper) woven mesh specification table**

**The materials of the wires for mesh are conforming to the requirements ASTM B134, B103**

Mesh Count	Aperture		Wire Diameter		Max Roll width	Weave type
	inch	mm	inch	mm		
4×4	0.1870	4.75	0.0630	1.600	1530	Plain
4×4	0.2030	5.15	0.0472	1.200	1530	Plain
5×5	0.1606	4.08	0.0394	1.000	1530	Plain
6×6	1.1200	3.343	0.0350	0.890	1530	Plain
8×8	2.1200	2.465	0.0280	0.710	1530	Plain
10×10	0.0800	2.03	0.0201	0.510	1530	Plain
12×12	0.0630	1.6	0.0200	0.508	1530	Plain
14×14	0.0510	1.3	0.0200	0.508	1530	Plain
16×16	0.0445	1.13	0.0180	0.457	1530	Plain
18×18	0.0386	0.98	0.0170	0.432	1530	Plain
20×20	0.0340	0.86	0.0160	0.406	1530	Plain
24×24	0.0277	0.7	0.0140	0.356	1530	Plain
30×30	0.0213	0.54	0.0120	0.305	1530	Plain
30×30	0.0243	0.62	0.0090	0.229	1530	Plain
40×40	0.0150	0.38	0.0100	0.254	1530	Plain
50×50	0.0120	0.31	0.0080	0.203	1530	Plain
60×60	0.0097	0.25	0.0070	0.178	1530	Plain
80×80	0.0077	0.197	0.0047	0.120	1530	Plain
90×90	0.0061	0.16	0.0050	0.127	1530	Plain
100×100	0.0060	0.15	0.0040	0.102	1530	Plain
100×100	0.0065	0.17	0.0035	0.089	1530	Plain
110×110	0.0051	0.1295	0.0040	0.102	1530	Plain
120×120	0.0046	0.1168	0.0037	0.094	1530	Plain
150×150	0.0041	0.1041	0.0024	0.060	1530	Plain
160×160	0.0038	0.0965	0.0025	0.064	1530	Plain
180×180	0.0033	0.0838	0.0023	0.058	1530	Plain
200×200	0.0029	0.0737	0.0021	0.053	1530	Plain
250×250	0.0024	0.061	0.0016	0.040	1300	Twill
270×270	0.0021	0.054	0.0016	0.040	1300	Twill
300×300	0.0018	0.0446	0.0016	0.040	1300	Twill
325×325	0.0017	0.0432	0.0014	0.036	1300	Twill
400×400	0.0015	0.033	0.0012	0.030	1300	Twill

Any interest, please feel free to contact us!

Dashang Wire Mesh

Email: sales@dashangmesh.com

Tel/Fax: 0086 318 7563319/7521333

Pho: 0086 18632807688

Industrial Woven Wire Mesh Solution!

