

Stainless steel filter mesh belt specifications

The materials of the wires for mesh are conforming to the requirements ASTM A580.

Mesh No.	Wire Diameter		Absolute	Nominal	Roll Width Max	Weave type
	inch	mm	µm	µm		
130×30	0.0079×0.0177	0.200×0.450	100-110	100	1300	Reverse Plain
128×36	0.0079×0.0157	0.200×0.400	80-90	80	1300	Reverse Plain
175×50	0.0059×0.0118	0.150×0.300	60-70	60	1300	Reverse Plain
290×60	0.0035×0.0090	0.090×0.230	43-51	51	1300	Reverse Plain
290×74	0.0035×0.0079	0.090×0.200	38-45	40	1300	Reverse Plain
625×105	0.0016×0.0055	0.042×0.140	23-28	25	1300	Reverse Plain
630×134	0.0015×0.0051	0.040×0.130	18-23	17	1300	Reverse Plain
720×150	0.0013×0.0043	0.035×0.110	16-20	14	1300	Reverse Plain

48×10	0.0200×0.0200	0.500×0.500	350-450	400	1300	Reverse Twill
72×15	0.0200×0.0200	0.500×0.500	250-350	300	1300	Reverse Twill
132×16	0.0140×0.0180	0.352×0.457	210-260	250	1300	Reverse Twill
132×18	0.0140×0.0179	0.355×0.455	180-220	200	1300	Reverse Twill
152×24	0.0120×0.0140	0.315×0.350	115-130	165	1300	Reverse Twill
260×40	0.0059×0.0086	0.150×0.220	80-95	125	1300	Reverse Twill
325×39	0.0059×0.0120	0.150×0.300	45-75	55	1300	Reverse Twill
345×45	0.0055×0.0090	0.140×0.230	40-65	50	1300	Reverse Twill
400×120	0.0026×0.0040	0.065×0.100	60-70	60	1300	Reverse Twill



Any interest, please feel free to contact us!

Dashang Wire Mesh

Email: sales@dashangmesh.com

Tel/Fax: 0086 318 7563319/7521333

Pho: 0086 18632807688

Industrial Woven Wire Mesh Solution!

